

CONTRACTOR REPORT

SAND82-7146
Unlimited Release
UC-63c

Concentrator Receiver Encapsulant Evaluation

Applied Solar Energy Corporation
15251 E. Don Julian Road
City of Industry, CA 91746

Prepared by Sandia National Laboratories Albuquerque, New Mexico 87185
and Livermore, California 94550 for the United States Department of Energy
under Contract DE-AC04-76DP00789

Printed February 1983

***When printing a copy of any digitized SAND
Report, you are required to update the
markings to current standards.***

Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

NOTICE: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof or any of their contractors or subcontractors.

Printed in the United States of America
Available from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22161

NTIS price codes
Printed copy: A02
Microfiche copy: A01

SAND82-7146
Unlimited Release
Printed February 1983

Distribution
Category UC-63c

Concentrator Receiver Encapsulant Evaluation

Applied Solar Energy Corporation
15251 E. Don Julian Road
City of Industry, CA 91746

Sandia Contract No. 68-9412

Abstract

During this contract, receivers and encapsulated cell strings were fabricated utilizing four (4) different encapsulating materials in accordance with BDM-PRDA 35 Receiver Design as defined in Sandia National Laboratories, Document No. 68-9412. Three five-cell laminated segments, two one-foot receiver assembly and one five-foot receiver assembly were fabricated using each of the four encapsulating materials. The segments and assemblies were delivered to Sandia National Laboratories, Albuquerque, New Mexico for testing and evaluation. A manufacturing cost comparison was made per five feet receiver using each of the four encapsulant materials and assuming 1MW/year production quantity.

TABLE OF CONTENTS

		<u>PAGE</u>
	ABSTRACT	i
	TABLE OF CONTENTS	ii
	LIST OF TABLES	iii
	LIST OF DRAWINGS	iv
1.0	INTRODUCTION	1
2.0	TECHNICAL DISCUSSION	1
2.1	Program Outline	1
	2.1.1 Task 1	1
	2.1.2 Task 2	2
	2.1.3 Task 3	2
	2.1.4 Task 4	2
2.2	Cell String & Module Segment Design	2
	2.2.1 Dow Corning Sylgard 184	3
	2.2.2 General Electric RTV-615	3
	2.2.3 McGhan Nu-Sil R-2602	4
	2.2.4 3M Film NPE-1677	4
3.0	COST ANALYSIS	5
4.0	CONCLUSIONS	5

LIST OF TABLES

		<u>PAGE</u>
1	Module Estimated Data	7
2	Cost of Common Materials and Common Labor Hour Requirement	8
3	Solar Cell Cost	9
4	Estimated Cost of Module (RTV0615 Encapsulant)	10
5	Estimated Cost of Module (RTV-2602 Encapsulant)	11
6	Estimated Cost of Module (Sylgard 184 Encapsulant)	12
7	Estimated Cost of Module (3M #NPE-1677 Encapsulant)	13
8	Module Cost	14

LIST OF DRAWINGS

		<u>PAGE</u>
I	D-202982-6 Laminate Assembly	15
II	D-202986-G Cell Module Assembly	16

1.0 INTRODUCTION

The objective of this work was to evaluate various encapsulants for the BDM-PRDA 35 PV receivers, using four different encapsulating materials. ASEC is to build three each five cell string laminates, two each one-foot receiver assembly segments, one each five-foot receiver assembly and deliver the items to Sandia National Laboratories to test and evaluate the encapsulating material. Furthermore, ASEC is to make an economic analysis of the cost per five feet receiver assembly for mass production using each of the four encapsulant. A secondary objective was to evaluate the method of application of the material.

2.0 TECHNICAL DISCUSSION

The PRDA 35 BDM receivers used polyvinyl butyral (PVB) as the encapsulant to bond the cell string to the Pyrex glass superstrate. When PVB is exposed to elevated temperature (120°C) in the presence of oxygen, the PVB will turn brown in color and/or bubble. Neither condition is desirable for concentrator applications. This program is to assess the suitability of other materials as the encapsulant. The following materials were to be evaluated:

- a) Dow Corning Sylgard 184.
- b) General Electric RTV 615
- c) McGhan NuSil R-2602
- d) 3M Film NPE-1677

2.1 Program Outline

The program consists of four (4) tasks.

2.1.1 Task 1

Under Task 1, ASEC fabricated three (3) each five-cell string laminates with each of the four materials listed above. The details of the laminates are shown

in ASEC Drawing D-202982. 10-inch long pigtails were attached to the laminates for electrical connection.

2.1.2 Task 2

Under Task 2, ASEC fabricated two (2) each, one-foot sections of the PRDA 35 BDM receivers using each of the four materials listed above as the encapsulant. The detailed receiver assembly is shown in ASEC Drawing D-202986. The extrusion is cut to one foot length and one (1) five (5) cell laminate is attached to each side of the extrusion.

2.1.3 Task 3

Under Task 3, ASEC fabricated one each five-foot receiver section using each of the four materials listed above as the encapsulant. The receiver assembly is shown in ASEC Drawing D-202986.

2.1.4 Task 4

Under Task 4, ASEC performed an economic analysis on a five foot receiver section using each of the four materials as the encapsulant.

2.2 Cell String And Module Segment Design

The cell stack assembly consists of Corning #7740 Pyrex glass superstrate, encapsulant and concentrator solar cell. The encapsulated cell string assembly is bonded to an anodized aluminum extrusion with Emerson-Cuming #4952 white thermally conductive RTV. 1.8 mil thick Kapton tape applied to the extrusion is used as the dielectric insulator. The specification and application of the encapsulation materials will be discussed in the following paragraphs.

2.2.1 Dow Corning Sylgard 184

Sylgard 184 is a high strength, room temperature curing silicone elastomer, supplied as a two component pourable system. It is a clear formulation with over 90% light transmission in a thin section and its index of refraction matches that of the glass. The room temperature curing time is high. It can be cured in elevated temperatures to shorten curing time. It has relatively low viscosity (800 CPS) which will be even lower under elevated temperature. The degassing time of the mixture is moderate, 5-10 minutes per 150 milligram in 30 inches of mercury vacuum. Because of the low viscosity, dammed fixturing is required to retain the Sylgard 184 in place. Also it requires the fixtures to be level. When a cell string is placed on top of the adhesive, small bubbles will appear between the cells and the glass. The bubbles are removed by applying pressure starting from one end of the cell string to the opposite end. The most time-consuming operation is to clean the encapsulated cell string assembly. Although the parts can be handled after one (1) hour of elevated temperature curing, complete curing will occur between 7-10 days at room temperature. Alcohol, MEK, Acetone, etc. cleansers must not be used for cleaning purposes because the uncured elastomer will absorb some quantities of solvent which will prevent complete curing of the adhesive.

2.2.2 General Electric RTV-615

It is a two component silicone elastomer formulated for room temperature curing. The basic viscosity is 5000 CPS. The light transmission and index of refraction are the same as those of Sylgard 184. RTV-615 has a very long (25-30 Min.) degassing time. Its application and fixturing are the same as those of Sylgard 184. The viscosity drops to 200-300PCS during temperature curing for a short period of time which may create voids or bubbles. The same technique

used with Sylgard 184 to remove bubbles may be used with RTV-615 and cleaning of parts is similar to that of Sylgard 184.

2.2.3 McGhan Nu-Sil R-2602

It is the direct descendant of the discontinued GE-RTV-602. The two component elastomer is formulated for room temperature curing or for moderate temperature curing with a different catalyst. The viscosity is 1200 CPS which immediately starts to increase after mixing and degassing. The degassing time is about 5 minutes. Application of R-2602 is the easiest among the three elastomers used in the program. However, the curing time to handle the part is very long 10-12 days to complete curing. Although the fixturing is not as critical as in the two previously described materials, it requires damming and leveling of the fixture. The cleaning of the encapsulated parts is the same as that of the Sylgard 184 or RTV-615.

2.2.4 3M Film NPE-1677

This is a proprietary formulation, heat-pressure sensitive, 15 mil thick film supplied on a polymeric carrier. The film is tacky to the touch and it is highly adhesive. The film is applied to the clean surface of the coverglass, the polymeric carrier is easily removable and then the cell string is placed over the film on the pre-determined area. No holding fixture or taping is required because of the high adhesion characteristic of the film. The parts now can be batch processed in temperature and pressure controlled equipment in a vacuum bag. Processing temperature is 150°C @ 100 PSI and 29 inches of mercury pressure in the vacuum bag. There is no after process cleaning required since the film does not melt or flow.

3.0 COST ANALYSIS

The cost of materials and the man hours required for manufacturing will be discussed in this paragraph. The analysis based on 1 MW per year production. Table No.1 shows the module parameters and the estimated module performance. From this figure, it is concluded that about 6.5 thousand modules are required to produce 1 MW of power. Assumption was made that state-of-the-art manufacturing technology would be used.

This cost analysis does not deal with equipment, tooling, etc. installation, G & A, or profit G & A, and structure of any manufacturing facility. It shows the cost of material which makes up the module and the estimated man hours required to complete a module. A labor rate of \$6.00/Hr. and an overhead rate of 250% were assumed for the calculation.

Table No.2 shows the cost of the common materials used in each of the four modules and shows the common labor hour requirement that is present in each module. Table 3 shows the concentrator cell cost. Tables 4,5,6, and 7 show the estimated cost of the modules with the four different encapsulation. Table 8 presents the module cost and the dollar per watt cost of the module.

4.0 CONCLUSION

RTV Silicone elastomers have been used for encapsulating solar cells especially in space panel fabrication. They have good weatherability, good thermal stability, and high resistance against UV radiation. All these characteristics are desirable for concentrator application. However, only very limited data is available yet of its long time endurance under concentrated sunlight. The difficulty in application, cleaning, etc., make the elastomers more difficult to automate and

less cost effective. A new application or processing technology has to be developed.

The economic analysis indicates the cell cost dominates the module cost which is relatively insensitive to the type of encapsulant chosen.

TABLE 1
MODULE ESTIMATED DATA

Module Parameters

44 Solar Cells, 22 On Each Side of the "V" Substrate:

Cell Size:	1.8 x 6.46cm Active Area
Connection:	22 in Series, Each Side
Diode:	(4) Four By-Pass Diode on Each Side, Internally Connected
Concentration Ratio:	27.75 Suns
Overall Length:	58 Inches

Estimated Performance

Efficiency:	13.5% @ 55 ⁰ C Cell Temperature
Insolation:	800 w/m ² = .08 w/cm ²
Module Output:	1.8 x 6.46 x .8 x .135 x 27.75 x 44 = 153.3W
1 mW =	Approximately 6.5 K Receiver

TABLE 2
COST OF COMMON MATERIALS AND COMMON
LABOR HOUR REQUIREMENT

COST OF MATERIAL PER MODULE

<u>Material Description</u>	<u>Unit Cost</u>	<u>Requirement</u>	<u>TOTAL</u>
Al Extrusion, Substrate	\$1.00/lb.	3.75 lb.	\$ 3.75
Pyrex Substrate	6.50 Ea.	8 Pcs.	52.00
Cu.Ribbon, Solder Clad	19.95/lb.	.32 lb.	6.40
End & Wire Cover, Die-Cast	.22 Ea.	4 Pcs.	.88
Diode, By-Pass	2.25 Ea.	8 Pcs.	10.25
Retainer Clips	.45 Ea.	36 Pcs.	16.20
Bonding, #4952 W RTV	13.50/lb.	.33 lb.	4.50
Insulating Tape, Misc.			6.50
Miscellaneous			1.75
			<hr/>
TOTAL			<u>\$102.23</u>

COMMON LABOR HR. REQUIREMENT PER MODULE

Substrate Machineing & Finishing	.42 Hr.
Soldering & Cleaning	.75 Hr.
Testing	.25 Hr.
Taping	.66 Hr.
Cell Assembly Lay Down	.30 Hr.
Dielectric & Functional Test	.10 Hr.
Final Assembly & Cleaning	2.20 Hrs.
Final Test (1 Sun)	<u>.10 Hr.</u>
TOTAL HOURS	4.78 Hr.

TABLE 3
SOLAR CELL COST

The following costs and rates are assumed.

High Purity Polysilicon	\$65/Kilogram
Labor Rate	\$ 6/Hour
Manufacturing Overhead	250%
Metallization	\$0.80/Cell

COST/CELL

Silicon	\$1.00
Metallization	.80
0.2 Hr/Cell	1.20
Overhead	<u>3.00</u>
	\$6.00

At 80% Yield	COST/CELL =	\$7.50
--------------	-------------	--------

TABLE 4
ESTIMATED COST OF MODULE

RTV-615 ENCAPSULANT

Basic Material Cost		\$102.23
Cost of RTV - 615	\$21.3/lb. @ .65 lb./Module	13.84
Lay-Up Tape		1.64
Primer		<u>.45</u>
TOTAL MATERIAL:		\$118.16

SOLAR CELL

Basic Labor Hour	4.78 Hr.
Lay-Up Prep.	.26 Hr.
Encapsulation (Elevated Temperature)	.40 Hr.
Cleaning	<u>.30 Hr.</u>
TOTAL HOURS:	\$5.74 Hr.

TABLE 5
ESTIMATED COST OF MODULE

RTV-2602 ENCAPSULANT

Basic Material Cost		\$102.23
RTV-2602	\$50.00/lb. @ .65 lb./Module	32.50
Lay-Up Tape		1.64
Primer		<u>.45</u>
TOTAL MATERIAL:		\$136.82

SOLAR CELL

Basic Labor Hour	4.78 Hr.
Lay-Up Prep	.26 Hr.
Encapsulation (Room Temperature	.56 Hr.
Cleaning	<u>.30 Hr.</u>
TOTAL HOURS:	5.90 Hr.

TABLE 6
ESTIMATED COST OF MODULE

SYLGARD 184 ENCAPSULANT

Basic Material Cost		\$102.23
Sylgard 184	\$20.2/lb. @ .65 lb./Module	13.13
Lay-Up Tape		1.64
Primer		<u>.45</u>
TOTAL MATERIAL:		\$117.45

SOLAR CELL

Basic Labor Hr.	4.78 Hr.
Lay-Up Prep	.26 Hr.
Encapsulation (Elev.Temp)	.40 Hr.
Cleaning	<u>.30 Hr.</u>
TOTAL HOURS:	5.74 Hrs.

TABLE 7
ESTIMATED COST OF MODULE

3-M #NPE-1677 ENCAPSULANT

Basic Material Cost		\$102.23
NPE-1677 Film	6.5/Yrd. ² @ \$.1 Yrd. ²	<u>.65</u>
TOTAL MATERIAL:		\$102.88


SOLAR CELL

Basic Labor Hr.	4.78 Hr.
Lay-Up	.05 Hr.
Encapsulation (Batch Process)	<u>.01 Hr.</u>
TOTAL HOURS:	4.84 Hrs.

TABLE 8
MODULE COST

	<u>RTV-615</u>	<u>RTV-2602</u>	<u>SYLGARD-184</u>	<u>NPE-1677</u>
Module Material Cost	\$108.16	\$136.82	\$ 117.45	\$102.88
Labor Cost *	120.54	123.90	120.54	101.64
Cost of 44 Cells	<u>330.00</u>	<u>330.00</u>	<u>330.00</u>	<u>330.00</u>
	\$558.70	\$590.72	\$ 567.99	\$534.52
At 95% Yield, Cost/Module	\$588.11	\$621.81	\$ 597.88	\$562.65
COST/WATT	\$ 3.84	\$ 4.06	\$ 3.90	\$ 3.67

*Assume \$6/Hr. and 250% Overhead



Section A-A
1867026

ITEM	QTY	DESCRIPTION	REMARKS
1	1	1867026-1	1867026-1
2	1	1867026-2	1867026-2
3	1	1867026-3	1867026-3
4	1	1867026-4	1867026-4
5	1	1867026-5	1867026-5
6	1	1867026-6	1867026-6
7	1	1867026-7	1867026-7
8	1	1867026-8	1867026-8
9	1	1867026-9	1867026-9
10	1	1867026-10	1867026-10
11	1	1867026-11	1867026-11
12	1	1867026-12	1867026-12
13	1	1867026-13	1867026-13
14	1	1867026-14	1867026-14
15	1	1867026-15	1867026-15
16	1	1867026-16	1867026-16
17	1	1867026-17	1867026-17
18	1	1867026-18	1867026-18
19	1	1867026-19	1867026-19

NOTES:
 1. PLACE ITEM 19 ON GLASS, BEFORE LAMINATION. TRIM PLUM WITH ENDS OF GLASS.
 2. PLACE ITEM 17 ON GLASS, AFTER LAMINATION. TRIM PLUM WITH GLASS.
 3. PLACE TEFLON TAPE ON GLASS AND FOLD OVER APEX AS SHOWN AFTER LAMINATION.
 4. CUT ITEM 8 IN HALF, SOLDER TO THE DIODE AND CELL INTERCONNECT AS SHOWN.
 5. FRONT VIEW SHOWN WITHOUT GLASS.
 6. DIODE TO BE SOLDERED IN PLACE AFTER LAMINATION IN AUTOCLAVE.

DISTRIBUTION LIST:

Acurex Corporation (3)
Attn: George Sutton
Bob Spencer
John Kull
485 Clyde Avenue
Mountain View CA 94042

Aerospace Corporation
Attn: Ed Simburger
2350 El Segundo Blvd.
El Segundo, CA 90266

Alliance Tool Corp.
Fresnel Optics Division
Attn: Helmut Walter
1300 Mt. Read Blvd.
Rochester, NY 14606

Applied Solar Energy Corp. (10)
Attn: Frank Ho
Ken Ling (9)
15251 E. Don Julian Road
City of Industry, CA 91746

ARCO Power Systems
Attn: Floyd Blake
Suite 307
7061 S. University Blvd.
Littleton, CO 80122

Arizona State University (2)
Attn: Charles Backus
Robert Sanderson
College of Engineering
Tempe, AZ 85281

Ray Bahm & Associates
Attn: Ray Bahm
2513 Kimberly Court NW
Albuquerque, NM 87130

Battelle
Attn: Don Carmichael
505 King Avenue
Columbus, OH 43201

The BDM Corporation (3)
Attn: Tim Lambariski
Wayne Kauffman
Bill Schwinkendorf
1801 Randolph Road SE
Albuquerque, NM 87111

Boeing Engineering & Const. Co.
Attn: Roger Gillette
P. O. Box 3707
Seattle, WA 98124

Burns & Roe, Inc. (2)
Attn: G. A. Fontana
800 Kinderkamack Road
Oradell, NJ 07649

Chevron Research (2)
Attn: John Cape
R. Creek
576 Standard Avenue
Richmond, CA 94802

Cyro Industries
697 Route 476
Clifton, NJ 07015

U. S. Dept. of Energy (2)
ALO
Attn: James Morley
Ethan Walker
P. O. Box 5400
Albuquerque, NM 87115

U. S. Dept. of Energy
Attn: John Hanson
Nuclear & Geosciences Div.
P. O. Box 5400
Albuquerque, NM 87115

U. S. Dept. of Energy (8)
Div. of PV Energy Technologies
Attn: R. Annan
M. Prince
L. Herwig (5)
A. Scolaro
1000 Independence Ave. SW
Washington, DC 20585

EPRI
P. O. Box 10412
Palo Alto, CA 84303

McGraw Hill
607 Boylston St.
Boston, MA 02116

E-Systems (2)
Attn: Mark O'Neill
A. J. McDanal
P. O. Box 226118
Dallas, TX 75266

3M
Attn: Sanford Cobb
Industrial Optics
235 2D15
3M Center
St. Paul, MN 55144

General Electric Co.
Attn: Ron Hodge
P. O. Box 527
King of Prussia, PA 19406

Motorola
Attn: Keith Kingston
GED
8201 E. McDowell
Scottsdale, AZ 85252

International Rectifier
Attn: Harold Weinstein
235 Kansas Street
El Segundo, CA 91214

NASA, HQ
Attn: John Loria
Code RET-1
Washington, DC 20546

Intersol Power Corporation
Attn: John Sanders
7400 W. Radcliff Avenue
Littleton, CO 80123

New Shelter Home Magazine
9317 Shoshone
Albuquerque, NM 87111

Jet Propulsion Lab (2)
Attn: K. Shimada
R. Ferber
4800 Oak Grove Drive
Pasadena, CA 91109

Oak Ridge National Lab
Attn: Steve Kaplan
P. O. Box X
Oak Ridge, TN 37830

Jet Propulsion Lab
Solar Data Center
MS 502-214
4800 Oak Grove Drive
Pasadena, CA 91106
J. Baumann
P. O. Box 179
Denver, CO 80201

Oklahoma University
571 South University Blvd.
Norman, OK

Photowatt (2)
Attn: William Taylor
Mike Keeling
2414 W. 14th Street
Tempe, AZ 85281

Martin Marietta (3)
Attn: R. Hein
D. Hughes
J. Baumann
P. O. Box 179
Denver, CO 80201

Power Hybrids
Attn: Jeff Meyer
1742 Crenshaw Blvd.
Torrance, CA 90501

Microwave Associates
Attn: Joel Goodrich
South Avenue MS-116
Burlington, MA 01803

PRC
Attn: E. Stirewalt
201 Leesburg Pike
Suite 400
Falls Church, VA 22070

Purdue University (2)
Attn: Richard Schwartz
Mark Lundstrom
Electrical Engineering Dept.
West Lafayette, IN 47907

Quantum Specialties
Attn: James E. Molle
163 Verde Circle
Rohnert Park, CA 94928

Research Triangle Institute
Attn: Mayrant Simons
Box 12194
Research Triangle Park, NC 27709

SERI (3)
Attn: Gene Blakeslee
Lee Cole
John Benner
1617 Cole Blvd.
Golden, CO 80401

SERI, Library (2)
1536 Cole Blvd., Bldg. #4
Golden, CO 80401

SOLAREX
Attn: John V. Goldsmith
1335 Piccard Dr.
Rockville, MD 20850

Solar Kinetics, Inc.
Attn: Gus Hutchison
Box 47045
Dallas, TX 75247

Solar Works
Attn: Paul Wilkins
Route 2, Box 274
Santa Fe, NM 87501

Southern Cal Edison
Attn: Spencer Carlisle
2244 Walnut Grove Ave.
Rosemead, CA 91770

Spectrolab
Attn: Brian Elm
12500 Gladstone Avenue
Sylmar, CA 91342

Spire (4)
Attn: S. Tobin
M. Nowlan
R. Little
S. Rechteris
Patriots Park
Bedford, MA 01730

Star Light Energy
Attn: J. Furber
1717 18th Street NW
Washington, DC 20009

Strategies Unlimited
201 San Antonio Circle
Suite 205
Mountain View, CA 94040

Thermo Electron
Attn: Ron Scharlack
45 First Avenue
Waltham, MA 02154

UNM/NMERI
Attn: G. Leigh
Campus Box 25
Albuquerque, NM 87131

Varian & Associates (2)
Attn: Peter Borden
N. Kaminar
611 Hansen Way K-219
Palo Alto, CA 94303

University of Wisconsin
Attn: Prof. J. D. Wiley
Dept. of Electrical Engineering
Madison, WI 53706

Wright Patterson AFB
Attn: Jack Geis
AFWAL/POOC
Wright Patterson AFB, OH

Wyle Labs (2)
Attn: Dave Christenson
George Meares
7800 Governors Drive West
Huntsville, AL 35807

1133 R. Chaffin
1133 J. Wiczer
1811 R. Assink
1811 C. Reuschler
1822 J. Sweet
Attn: M. Moss
R. Pettit
1823 M. Chamberlain
1845 R. Eagan
2146 M. Garner
2146 B. Nasby
2146 J. Rodriguez
2146 H. Weaver
9700 E. Beckner
9720 D. Schueler
9721 J. Banas
9721 H. Gerwin
9723 E. Burgess
9724 E. Boes
9723 C. Rogers
9724 D. Arvizu
9724 L. Beavis
9724 C. Chiang
9724 M. Edenburn
9724 B. Hanson
9724 D. King
9724 A. Maish
9724 M. Rios
9724 B. Rose
9724 R. Siegel
9724 C. Stillwell
3141 L. J. Erickson (5)
3151 W. L. Garner (3)
3154-3 C. H. Dalin (25)
For DOE/TIC (Unlimited Release)
8214 M. A. Pound